

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009498 A1

(51) International Patent Classification⁷: C02F 1/46, 1/461

(21) International Application Number:
PCT/GB2003/003540

(22) International Filing Date: 21 July 2003 (21.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0217268.2 23 July 2002 (23.07.2002) GB

(71) Applicant and

(72) Inventor: CROSS, David, Edward [GB/GB]; Hedge
End, Hurst Road, East Preston, Littlehampton, West
Sussex BN16 3AP (GB).

(74) Agent: COLES, Graham, Frederick; Graham Coles &
Co, 24 Seeleys Road, Beaconsfield, Buckinghamshire HP9
1SZ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTROCHEMICAL CELLS



(57) **Abstract:** An electrochemical cell has an inner, titanium-rod electrode (1) mounted coaxially within an outer, titanium-tube electrode (2) with a porous, ceramic tube (3) mounted coaxially between them to define coaxial, annular passageways (4,5) for liquid flow in separate streams lengthwise of the cell between respective pairs of inlet/outlet ports (6, 6; 7, 7). A cup-shape fitting (8) having a stepped-down internal diameter is clamped onto the rod electrode (1) at each end of the cell, with the tubular electrode (2) at that end held tightly sealed in the mouth (14) of the fitting (8). Each end of the ceramic tube (3) projects into the larger-diameter cavity-part (10) of the fitting (8) at that end and has a radial flange (17) that provides a sliding seal within this cavity-part (10) for keeping the inlet/outlet ports (6,7) for the respective liquid streams at that end, divided off from one another as well as allowing the ceramic tube (3) limited freedom for longitudinal sliding relative to the electrodes (1, 2).

BEST AVAILABLE COPY